



Power supply

Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional

Category

Category:	Display devices
Product Group:	Display device

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	325 x 190 x 225 mm
Gross weight:	1,400 kg
Net weight:	1,500 kg
Shipping method:	Parcel service

Construction

Dimensions housing (WÄDÄH):	260 x 150 x 65 mm
Dimensions of display device (WÄDÄH):	260 x 150 x 65 mm
Wall mount:	yes

Measuring system

Adjustment options:	External calibration
Linearisation (points):	4
Number of weighing ranges:	2
Resolution (non verifiable):	60000
Resolution (verifiable):	3000
Weighing units:	g kg

Display

Display digit height:	1,650 cm
Display digit height:	1,300 cm

Technical data about verification

Verification approval conforming to 90/384/EEC:	yes
Verification class:	III

Functions

Counting function:	yes
Data hold function:	yes
Function to save totals:	yes
Percentage determination:	yes
PRE-TARE function:	yes
SLEEP function:	yes
Weighing with tolerance range:	yes

Environmental conditions

Maximum operating temperature:	40 °C
Minimum ambient temperature:	0 °C